

Multiple socket outlet modular MEDX ZPA



Modular. Individual. Unique.

The multiple socket outlet MEDX ZPA offers customized solution for your system. This multiple socket outlet fits in terms of load and place ideal for changing circumstances. The unique construction allows an customised manufacturing, without renouncing important features. Each module has an additional potential equalization and two fuse-links. Your electrical system is optimally protected against failure.

A further advantage is the additional potential equalization on the housing so that the multiple socket outlet multiple socket outlet can be used simultaneously as a local ZPA distributor.

Advantages:


- VDE power sockets with VDE seal of approval
- Each power socket redundantly-fused
- 2.5 mm² thick cable with anti-kink protection
- Safety lock for preventing accidental modification of the electrical system
- TÜV tested for use with anaesthesia equipment

Perfection through versatility

Secure Systems: The multiple socket outlet MEDX ZPA impresses with its versatility and can perfectly be adapted to your system. According to the modular principle, up to 8 modules can be manufactured to a multiple socket outlet with a power cable of three or five meters. Each module is equipped with a single Guard KIT, to prevent accidental changes of the electrical system.

The modular multiple socket outlet concept offers a cost-effective solution that allows to procure only the required number of socket outlets.

Subsequent extensions of your electrical system do not require a new multiple socket outlet. The missing module can be extended by us.



Features




Modular – as required available with 1 up to 8 socket outlets. Inclusive additional potential equalization for each socket insert.



2 fuses per socket insert for immediate detection of failures. Replaceable during operation.



Safety locks for preventing modifications of the electrical system.



Additional potential equalization on the case, and 11 mm thick power cable with 2.5 mm² single lines and kink protection on the housing.

Options



Circuit breaker module

Resettable thermal protection, 14 A, (D)
Art. No. 2012264
8 A, (CH)
Art. No. 2012399



Circuit breaker module

Switchable thermal protection with push buttons, 14 A (D)
Art. No. 2012258




USB charging module

2-way USB A module.
DC 5.1 V, max. 4 A,
20.4 W total
Art. No. 2012432

Technical data

MEDX ZPA

Fuse protection power socket insert	2 microfuses, each 5x 20 mm (DIN EN 60127-2/VDE 0820-2)						
ZPA (PE) connector	according to DIN 42801						
Cable length	3 m 5 m						
Number of modules min	1						
Number of modules max	8						
Total load each sockets	1400 W max. (D), 750 W max. (CH)						
Total load multiple socket outlet	3600 W max. without thermal circuit breaker 3300 W max. (D), 1800 W max. (CH) when using modules with thermal circuit breaker						
Dimensions per modul in mm (LDH)	90x 79x 60						
Total dimensions in mm	1 Module	A 79	B 90	C 110	D 198	E 60	F 80
	2 Modules	A 79	B 160	C 180	D 268	E 60	F 80
	3 Modules	A 79	B 230	C 250	D 338	E 60	F 80
	4 Modules	A 79	B 300	C 320	D 408	E 60	F 80
	5 Modules	A 79	B 370	C 390	D 478	E 60	F 80
	6 Modules	A 79	B 440	C 460	D 548	E 60	F 80
	7 Modules	A 79	B 510	C 530	D 618	E 60	F 80
	8 Modules	A 79	B 580	C 600	D 688	E 60	F 80
Case	Anodized aluminum						
Standards	tested according to IEC IEC 60601-1:2005 IEC 60601-1:2005/AMD1:2012 IEC 60601-1:2005/AMD2:2012/AMD2:2020 ISO 80601-2-13:2011 / A1:2015 with the exception of clause 201.11.6.3 (Liquid ingress).ISO 80601-2-12:2011/AMD2:2018						
Delivery per modul	1x individual multiple socket outlet *, 1x MEDX ZPA single guard kit green, 1x tee-handled socket wrench						

Accessories



Safety locks

To prevent accidental pulling out or adding of SCHUKO plugs.

- 1** MEDX green removal protection kit, covers: 1 power socket
1 ea. per modul in the scope of delivery of the MEDX ZPA.
Order number: 2011468

Mounting plate

Universal mounting plate for wall mount or with additional accessories on standard rails or poles. Incl. screws.

Dimensions WxHxD in mm: 79x84x6

A second mounting plate is recommended for 3 or more modules

- 2** Order number: 2012585

Set microfuse MEDX/MED5

Set of 10 microfuses. Accessory for the multiple sockets MEDX and MED5 ZPA.

Tripping characteristic: slow blow -T-, Fuse construction: ceramic tube with extinguishing medium

- 3** 6.3 A Order number: 2012828

Pipe mounting

Clamp for a standard < 40mm. This clamp can be connected to the mounting bracket. Mounting diameter max. 40mm. In combination with mounting plate (order number 2012585).

- 4** A second pipe mounting is recommended for 3 or more modules.
Dimensions WxHxD in mm: 42x80/150-190x48
Order number: 2006327

Tee-handled socket wrench

For the easy loosening and attachment of the guard bracket on the MEDX ZPA multiple socket outlet.

- 1 ea. in the scope of delivery of the MEDX ZPA.
5 Order number: 2007233

Standard rails clips (2 ea.)

2 standard rails clips for mounting the multiple socket outlet to standard rails. In combination with mounting plate (order number 2012585).

- A second mounting plate is recommended for 3 or more modules
Dimensions WxHxD in mm: 35x50x30
Order number: 2007208